

12
kW

POWERPROTECT™ DX
Standby Generators



YOU.POWERED.™

RESIDENTIAL Standby Generators



SPECIFICATIONS

OVERVIEW

Brand	Briggs & Stratton®
Series Name	Power Protect™
Model Name	PPDX12
Model Number	040669
Rated AC Voltage (Volts)	120 / 240
Frequency (Hz)	60
Generator Breaker (Amps)	60
Operating Ambient Temperature (°C / °F)	-28 - 40 / -20 - 104
Running Amperage, Standby (LP / NG) (Amps)	50 / 45
Running Watts, Standby (LP / NG) (kW)	12 ¹ / 10.8
Power Factor	1.0
Exercise Duration	16 seconds

Engine

Engine Brand/Manufacturer	Vanguard®
Model Type	M38
Aspiration	Naturally Aspirated
Speed (RPM)	3600
Displacement (ci/cc)	38 / 623
Compression Ratio	8.3:1
Governor Type	Electronic

12

kW

POWERPROTECT[®] DX
Standby Generators
RESIDENTIAL STANDBY GENERATORS SPECIFICATIONS



Engine	
Bore & Stroke (mm / in)	75.5 x 70.1 / 2.97 x 2.76
Cylinder Block	Aluminum with Cast Iron Sleeve
Valve Arrangement	OHV
Engine Cylinder Configuration	V
Number of Cylinders	2
Start Type	Automatic
Frequency Regulation Steady State, No Load to Full Load (%)	+/- 1.0
Air Filter Type	Dry
Low Oil Pressure Switch	Yes
Engine Oil Heater	Yes
Rated Temperature (°C / °F)	25 / 77
Sound Rating ²	
Low Idle Mode Sound dB(A)	64
Normal Operating Sound ² dB(A)	70
Lubrication System	
Type	Full Pressure
Oil Capacity (oz / L)	48 / 1.42
Oil Filter (Quantity / Type)	1 / Cartridge
Oil Brand	Schaeffer
Recommended Oil	5W30 Full Synthetic
Electrical System	
Ignition System	Fixed Timing
Battery Quantity	1
Battery Voltage (VDC)	12
Battery CCA (Amps)	540
Battery Grouping Size	26 or 51
Starter Motor Voltage (VDC)	12
Fuel System	
Fuel Type	NG / LPV
Fuel Supply Line Inlet	3/4" NPT
Recommended Fuel, Lower Heating Value Minimum (MJ/m ³ / BTU/ft ³)	NG: 34.3 / 904 LPV: 87.1 / 2338
Fuel Supply Pressure (mbar / in H ₂ O)	NG: 9-17 / 3.5-7 LPV: 28-34 / 11-14

12

kW

POWERPROTECT[®] DX
Standby Generators
RESIDENTIAL STANDBY GENERATORS SPECIFICATIONS



Fuel Consumption ¹	
No Load, NG (BTU/hr)	66,000
No Load, NG (ft ³ /hr)	66
Half Load, NG (BTU/hr)	117,000
Half Load, NG (ft ³ /hr)	117
Full Load, NG (BTU/hr)	172,000
Full Load, NG (ft ³ /hr)	172
No Load, LP (BTU/hr)	57,000
No Load, LP (ft ³ /hr)	23
No Load, LP (gal/hr)	0.70
Half Load, LP (BTU/hr)	155,000
Half Load, LP (ft ³ /hr)	62
Half Load, LP (gal/hr)	1.7
Full Load, LP (BTU/hr)	209,000
Full Load, LP (ft ³ /hr)	84
Full Load, LP (gal/hr)	2.3
Alternator Specifications	
Alternator Type	Self-Excited, Rotating Field
Alternator Manufacturer	Briggs & Stratton
Frequency (Hz)	60
Phase	1
Insulation Rating (Class)	F
Designed Temperature Rise (°C)	105
Bearing (Quantity / Type)	1 / Sealed
Number of Poles	2
Voltage Regulator	Brushed / Electronic
Motor Starting Capability (kVA)	37 (35% Voltage Dip)
Total Harmonic Distortion (THD), NL to FL (%)	< 5
Controls/Instrumentation	
Controller	GC-1032
Charger	Stand Alone
Starting	AMF or 2-wire
LED Digital Display	Yes
Alternator Frequency	Yes
Real Time Clock	Yes
Engine Hour Counter	Yes

12

kW

POWERPROTECT[®] DX
Standby Generators
RESIDENTIAL STANDBY GENERATORS SPECIFICATIONS



Controls/Instrumentation		
Engine Runtime Scheduler		Yes
Low Oil Pressure Shutdown		Yes
High Temperature Shutdown		Yes
Fault Code Display		Yes
Other Features		
Battery Rack and Cables		Yes
Fuel Solenoid Valve		Yes
Integral Vibration Isolation		Yes
Oil Drain Extension		Yes
Operation and Installation Manual(s)		Yes
Wind Speed Rating (mph)		175
Accessories		
Battery Warmer		6578
Maintenance Kit		6035
Fuel Regulator Warmer		6845
Surge Protector		6631
Gateway		6520
UPS		6581
InfoHub™ Universal - Cellular		6574
Gateway Range Extender		6839
Limited Warranty ⁴		
Warranty: Generator, Domestic & Canada (Parts / Labor / Travel) – Years		10
Warranty: Generator, International (Parts / Labor / Travel) – Years/Hours		10
Warranty: Enclosure, Surface Rust and Corrosion (Parts / Labor / Travel) – Years		1
Warranty: Enclosure, Rust Through (Parts / Labor / Travel) – Years		2
Certifications		
UL		Yes
cUL		Yes
Massachusetts Plumbers and Gasfitters Listing		Yes

12

kW

POWERPROTECT[®] DX


Standby Generators

RESIDENTIAL STANDBY GENERATORS SPECIFICATIONS



Weights & Dimensions

Assembled Dimensions (Length x Width x Height) (in / mm)	28 x 24.5 x 37.2 / 712 x 622 x 944
Assembled Weight (lbs / kg)	361 / 164
Packaged Dimensions (Length x Width x Height) (in / mm)	39 x 33.5 x 45 / 991 x 851 x 1143
Packaged Weight (lbs / kg)	423 / 192
Outline and Pad Layout Drawing	80104459



¹ This generator is rated in accordance with UL (Underwriters Laboratories) 2200 (stationary engine generator assemblies) and CSA (Canadian Standards Association) standard C22.2 No. 100-14 (motor and generators).

² Per ISO 3744, Sound level measurement at other locations around generator may differ depending on installation, based on lowest microphone at 7m. Normal operation based on average household usage.

³ Fuel consumption rates are estimated based on normal operating conditions. Generator operation may be greatly affected by elevation and the cycling operation of multiple electrical appliances — fuel flow rates may vary depending on these factors.

⁴ See operator's manual or BRIGGSandSTRATTON.com for complete warranty details.

Briggs & Stratton has a policy of continuous product improvement and reserves the right to modify its specifications at any time and without prior notice.

This standby generator is not for Prime Power applications.

Published August 2021. Please visit BRIGGSandSTRATTON.com for the latest information.

BS1303 - 8/21

BRIGGS & STRATTON
POST OFFICE BOX 702
MILWAUKEE, WI 53201 USA

Copyright © 2021 Briggs & Stratton. All rights reserved.